

*The NH-2100T offers the best value for a retail, through-the-wall ATM with an efficient yet flexible design.*

## **Features**

### **Reliability**

The NH-2100T has a proven track record for reliability with a Transreflective LCD or optional high-bright display. Its water-proof construction ensures operation in all climates.

### **Security**

This model ensures a safe transaction environment with a UL291 business-hour safe and PCI EPP (Encrypting PIN pad).

### **Small Size, Powerful Technology**

The compact size of the NH-2100T makes it ideal for smaller through-the-wall settings. It can hold up to 2,000 notes and includes a 200-note reject bin. Plus, it features a sunlight-viewable display; a bright display is optional.



***Superior quality, security and value.***

***Only with Nautilus Hyosung.***

*Now offering the most complete line of financial and retail ATMs.*



**The NH-2100T is a smart through-the-wall choice when compact size and affordable cost are important.**

### **Dependable Customer Service**

You can't afford ATM downtime. That's why we offer customer service with real people and real solutions. Trust Nautilus Hyosung to be your business partner.

# MONIMAX 2100T

## System Control

- Intel® 80186 Processor
- Embedded platform

## Customer Display

- 5.7" monochrome transreflective LCD
- Optional 5.7" high-bright EL Display

## Communication

- Dial-up

## Input Type

- 4 x 2 function keys
- 4 x 4 numeric keys
- PCI EPP (Encrypting PIN pad)
- ADA compliant

## Supervisor Operation

- Customer display
- Optional service rear panel

## Supports Five Languages

- English
- Spanish
- Japanese
- Korean
- French

## Card Handling

- Dip-type card reader
- Optional IC card reader, EMV Level 1, 2

## Cash Dispensing

- 2,000-note cassette

## Printer

- 3.1" graphical thermal receipt printer

## Security

- UL291 business hour safe
- Mechanical combination lock
- Optional electronic safe lock

## Miscellaneous

- Illuminated signage
- Adjustable pedestal

## Power Supply

- AC 110–230V, 50–60 Hz

## Operating Environment

- Temperature: 40°F–95°F
- Humidity: 15%–85%

## Dimension and Weight

- Height: 31.5" (800 mm)
- Width: 20" (508 mm)
- Depth: 28.5" (724 mm)
- Weight: 283 lbs (128 kg)
- Wall thickness 4"–10"

Internal components may change with the introduction of new technology. Nautilus Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.



**Nautilus**  
HYOSUNG

Contact your authorized Nautilus Hyosung distributor or representative for more information.