

*The Monimax 5100T is a high-value, through-the-wall ATM that features advanced performance, exceptional reliability, and a wide variety of optional modules. This ATM can easily scale up after installation to suit growing demand.*

## Features

### Powerful Performance

A Windows® open platform can handle any application software based on a WOSA/XFS platform. Opt for decreased transaction time, multi-media advertisements, and other advanced services and functions.

### Multipurpose

Walk-up, drive-up, through-the-wall, and free-standing kiosk—all are available with the Monimax 5100T. It features a small footprint and compact architecture that offers flexible options at an affordable price.

### Small Size, Large Display

An optional 10.4" sunlight-viewable color display is designed to perform clearly—inside or outside.

**Superior quality, security and value.**

**Only with Nautilus Hyosung.**

*Now offering the most complete line of financial and retail ATMs.*



**The Monimax 5100T helps you build your ATM revenue with an affordable option that includes easy scalability.**

### Dependable Customer Service

You can't afford ATM downtime. That's why we offer customer service with real people and real solutions. Trust Nautilus Hyosung to be your business partner.

# MONIMAX 5100T

## System Control

- Intel® Pentium®-IV processor
- Microsoft® Windows XP® platform

## Customer Display

- 10.4" color TFT LCD
- Optional sunlight viewable

## Communication

- TCP/IP or Dial-up

## Input Type

- 4 x 2 function keys
- 4 x 4 numeric keys
- PCI EPP (Encrypting PIN pad)
- ADA compliant

## Card Handling

- Dip-type card reader
- Optional IC card reader, EMV Level 1, 2

## Cash Dispensing

- 2,000-note cassette
- Up to four cassettes
- Note-by-note rejection

## Printers

- 3.1" graphical thermal receipt printer

## Security

- UL291 Business hours
- Standard mechanical safe lock
- Voice guidance system
- Optional UL291 Level 1
- Optional KABA Mas Cencon safe lock
- Optional electronic safe lock
- Optional key-combo safe lock

## Power Supply

- AC 110–230V, 50–60 Hz

## Operating Environment

- Temperature: 32°F–104°F
- Optional Tolerance: 14°F–104°F
- Humidity: 25%–86%

## Dimension and Weight

- Height: 59.4" (1509.5 mm)
- Width: 23.6" (600 mm)
- Depth: 32.6" (828 mm)
- Weight: 441.5 lbs (200 kg)

## Supervisor Operation

- 2 lines of 10 characters/line LCS
- Portable type, 16 keys

Internal components may change with the introduction of new technology. Nautilus Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.



Contact your authorized Nautilus Hyosung distributor or representative for more information.